

AS568 dash number appears to the right of Oring inside diameter (I.D.) and below cross sectional diameter.

| Cross Section | | | | | Cross Section | | | | | | Cross Section | | | | |
|---------------|--------|--------|--------|--------|---------------|--------|--------|--------|--------|--------|---------------|--------|--------|--------|--------|
| I.D. | 1/16 | 3/32 | 1/8 | 3/16 | I.D. | 1/16 | 3/32 | 1/8 | 3/16 | 1/4 | I.D. | 3/32 | 1/8 | 3/16 | 1/4 |
| | (.070) | (.103) | (.139) | (.210) | | (.070) | (.103) | (.139) | (.210) | (.275) | | (.103) | (.139) | (.210) | (.275) |
| 1/32 | 001* | | | | 2 3/16 | | 139 | | | | 7 | 167 | 262 | 365 | 441 |
| 3/64 | 002* | | | | 2 1/4 | 035 | 140 | 228 | 331 | | 7 1/4 | 168 | 263 | 366 | 442 |
| 1/16 | 003 | 102 | | | 2 5/16 | | 141 | | | | 7 1/2 | 169 | 264 | 367 | 443 |
| 5/64 | 004 | | | | 2 3/8 | 036 | 142 | 229 | 332 | | 7 3/4 | 170 | 265 | 368 | 444 |
| 3/32 | 005 | 103 | | | 2 7/16 | | 143 | | | | 8 | 171 | 266 | 369 | 445 |
| 1/8 | 006 | 104 | | | 2 1/2 | 037 | 144 | 230 | 333 | | 8 1/4 | 172 | 267 | 370 | |
| 5/32 | 007 | 105 | | | 2 9/16 | | 145 | | | | 8 1/2 | 173 | 268 | 371 | 446 |
| 3/16 | 008 | 106 | 201 | | 2 5/8 | 038 | 146 | 231 | 334 | | 8 3/4 | 174 | 269 | 372 | |
| 7/32 | 009 | 107 | | | 2 11/16 | | 147 | | | | 9 | 175 | 270 | 373 | 447 |
| 1/4 | 010 | 108 | 202 | | 2 3/4 | 039 | 148 | 232 | 335 | | 9 1/4 | 176 | 271 | 374 | |
| 5/16 | 011 | 109 | 203 | | 2 13/16 | | 149 | | | | 9 1/2 | 177 | 272 | 375 | 448 |
| 3/8 | 012 | 110 | 204 | | 2 7/8 | 040 | 150 | 233 | 336 | | 9 3/4 | 178 | 273 | 376 | |
| 7/16 | 013 | 111 | 205 | 309 | 3 | 041 | 151 | 234 | 337 | | 10 | | 274 | 377 | 449 |
| 1/2 | 014 | 112 | 206 | 310 | 3 1/8 | | | 235 | 338 | | 10 1/2 | | 275 | 378 | 450 |
| 9/16 | 015 | 113 | 207 | 311 | 3 1/4 | 042 | 152 | 236 | 339 | | 11 | | 276 | 379 | 451 |
| 5/8 | 016 | 114 | 208 | 312 | 3 3/8 | | | 237 | 340 | | 11 1/2 | | 277 | 380 | 452 |
| 11/16 | 017 | 115 | 209 | 313 | 3 1/2 | 043 | 153 | 238 | 341 | | 12 | | 278 | 381 | 453 |
| 3/4 | 018 | 116 | 210 | 314 | 3 5/8 | | | 239 | 342 | | 12 1/2 | | | | 454 |
| 13/16 | 019 | 117 | 211 | 315 | 3 3/4 | 044 | 154 | 240 | 343 | | 13 | | 279 | 382 | 455 |
| 7/8 | 020 | 118 | 212 | 316 | 3 7/8 | | | 241 | 344 | | 13 1/2 | | | | 456 |
| 15/16 | 021 | 119 | 213 | 317 | 4 | 045 | 155 | 242 | 345 | | 14 | | 280 | 383 | 457 |
| 1 | 022 | 120 | 214 | 318 | 4 1/8 | | | 243 | 346 | | 14 1/2 | | | | 458 |
| 1 1/16 | 023 | 121 | 215 | 319 | 4 1/4 | 046 | 156 | 244 | 347 | | 15 | | 281 | 384 | 459 |
| 1 1/8 | 024 | 122 | 216 | 320 | 4 3/8 | | | 245 | 348 | | 15 1/2 | | | | 460 |
| 1 3/16 | 025 | 123 | 217 | 321 | 4 1/2 | 047 | 157 | 246 | 349 | 425 | 16 | | 282 | 385 | 461 |
| 1 1/4 | 026 | 124 | 218 | 322 | 4 5/8 | | | 247 | 350 | 426 | 16 1/2 | | | | 462 |
| 1 5/16 | 027 | 125 | 219 | 323 | 4 3/4 | 048 | 158 | 248 | 351 | 427 | 17 | | 283 | 386 | 463 |
| 1 3/8 | 028 | 126 | 220 | 324 | 4 7/8 | | | 249 | 352 | 428 | 17 1/2 | | | | 464 |
| 1 7/16 | | 127 | 221 | | 5 | 049 | 159 | 250 | 353 | 429 | 18 | | 284 | 387 | 465 |
| 1 1/2 | 029 | 128 | 222 | 325 | 5 1/8 | | | 251 | 354 | 430 | 18 1/2 | | | | 466 |
| 1 9/16 | | 129 | | | 5 1/4 | 050 | 160 | 252 | 355 | 431 | 19 | | | 388 | 467 |
| 1 5/8 | 030 | 130 | 223 | 326 | 5 3/8 | | | 253 | 356 | 432 | 19 1/2 | | | | 468 |
| 1 11/16 | | 131 | | | 5 1/2 | | 161 | 254 | 357 | 433 | 20 | | | 389 | 469 |
| 1 3/4 | 031 | 132 | 224 | 327 | 5 5/8 | | | 255 | 358 | 434 | 21 | | | 390 | 470 |
| 1 13/16 | | 133 | | | 5 3/4 | | 162 | 256 | 359 | 435 | 22 | | | 391 | 471 |
| 1 7/8 | 032 | 134 | 225 | 328 | 5 7/8 | | | 257 | 360 | 436 | 23 | | | 392 | 472 |
| 1 15/16 | | 135 | | | 6 | | 163 | 258 | 361 | 437 | 24 | | | 393 | 473 |
| 2 | 033 | 136 | 226 | 329 | 6 1/4 | | 164 | 259 | 362 | 438 | 25 | | | 394 | 474 |
| 2 1/16 | | 137 | | | 6 1/2 | | 165 | 260 | 363 | 439 | 26 | | | 395 | 475 |
| 2 1/8 | 034 | 138 | 227 | 330 | 6 3/4 | | 166 | 261 | 364 | 440 | | | | | |

*Section diameter of AS568-001 is 1/32 Section diameter of AS568-002 is 3/64